

ESTIMATING TABLE
A7+
28 Fluid Ounce Cartridge
Number of Anchoring Installations per Cartridge*
Using Reinforcing Bar with A7+ Adhesive in Solid Concrete

REBAR	DRILL HOLE DIA. INCHES	EMBEDMENT DEPTH IN INCHES (mm)														
		1 (25.4)	2 (50.8)	3 (76.2)	4 (101.6)	5 (127.0)	6 (152.4)	7 (177.8)	8 (203.2)	9 (228.6)	10 (254.0)	11 (279.4)	12 (304.8)	13 (330.2)	14 (355.6)	15 (381.0)
#3	7/16	560.3	280.2	186.8	140.1	112.1	93.4	80.0	70.0	62.3	56.0	50.9	46.7	43.1	40.0	37.4
10M	9/16	339.0	169.5	113.0	84.7	67.8	56.5	48.4	42.4	37.7	33.9	30.8	28.2	26.1	24.2	22.6
#4	5/8	274.6	137.3	91.5	68.6	54.9	45.8	39.2	34.3	30.5	27.5	25.0	22.9	21.1	19.6	18.3
#5 or 15M	3/4	190.7	95.3	63.6	47.7	38.1	31.8	27.2	23.8	21.2	19.1	17.3	15.9	14.7	13.6	12.7
#6 or 20M	7/8	140.1	70.0	46.7	35.0	28.0	23.3	20.0	17.5	15.6	14.0	12.7	11.7	10.8	10.0	9.3
#7	1	107.2	53.6	35.7	26.8	21.4	17.9	15.3	13.4	11.9	10.7	9.7	8.9	8.2	7.7	7.1
#8 or 25M	1 1/8	84.7	42.4	28.2	21.2	16.9	14.1	12.1	10.6	9.4	8.5	7.7	7.1	6.5	6.1	5.6
#9	1 1/4	68.6	34.3	22.9	17.2	13.7	11.4	9.8	8.6	7.6	6.9	6.2	5.7	5.3	4.9	4.6
#10 or 30M	1 3/8	56.7	28.4	18.9	14.2	11.3	9.5	8.1	7.1	6.3	5.7	5.2	4.7	4.4	4.1	3.8
#11	1 3/4	35.0	17.5	11.7	8.8	7.0	5.8	5.0	4.4	3.9	3.5	3.2	2.9	2.7	2.5	2.3

* The number of anchoring installations is based upon calculations of hole volumes using ANSI tolerance carbide tipped drill bits, the nominal areas of the reinforcing bars and the stress areas of the threaded rods. These estimates do not account for waste.

ESTIMATING TABLE
A7+
28 Fluid Ounce Cartridge
Number of Anchoring Installations per Cartridge*
Using Threaded Rod with A7+ Adhesive in Solid Concrete

THREADED ROD	DRILL HOLE DIA. INCHES	EMBEDMENT DEPTH IN INCHES (mm)														
		1 (25.4)	2 (50.8)	3 (76.2)	4 (101.6)	5 (127.0)	6 (152.4)	7 (177.8)	8 (203.2)	9 (228.6)	10 (254.0)	11 (279.4)	12 (304.8)	13 (330.2)	14 (355.6)	15 (381.0)
1/4	5/16	1098.2	549.1	366.1	274.6	219.6	183.0	156.9	137.3	122.0	109.8	99.8	91.5	84.5	78.4	73.2
3/8	7/16	560.3	280.2	186.8	140.1	112.1	93.4	80.0	70.0	62.3	56.0	50.9	46.7	43.1	40.0	37.4
1/2	9/16	339.0	169.5	113.0	84.7	67.8	56.5	48.4	42.4	37.7	33.9	30.8	28.2	26.1	24.2	22.6
5/8	11/16	226.9	113.5	75.6	56.7	45.4	37.8	32.4	28.4	25.2	22.7	20.6	18.9	17.5	16.2	15.1
	3/4	190.7	95.3	63.6	47.7	38.1	31.8	27.2	23.8	21.2	19.1	17.3	15.9	14.7	13.6	12.7
3/4	13/16	162.5	81.2	54.2	40.6	32.5	27.1	23.2	20.3	18.1	16.2	14.8	13.5	12.5	11.6	10.8
	7/8	140.1	70.0	46.7	35.0	28.0	23.3	20.0	17.5	15.6	14.0	12.7	11.7	10.8	10.0	9.3
7/8	15/16	122.0	61.0	40.7	30.5	24.4	20.3	17.4	15.3	13.6	12.2	11.1	10.2	9.4	8.7	8.1
	1	107.2	53.6	35.7	26.8	21.4	17.9	15.3	13.4	11.9	10.7	9.7	8.9	8.2	7.7	7.1
1	1-1/16	95.0	47.5	31.7	23.8	19.0	15.8	13.6	11.9	10.6	9.5	8.6	7.9	7.3	6.8	6.3
	1-1/8	84.7	42.4	28.2	21.2	16.9	14.1	12.1	10.6	9.4	8.5	7.7	7.1	6.5	6.1	5.6
1-1/4	1-1/3	62.3	31.1	20.8	15.6	12.5	10.4	8.9	7.8	6.9	6.2	5.7	5.2	4.8	4.4	4.2
	1-3/8	56.7	28.4	18.9	14.2	11.3	9.5	8.1	7.1	6.3	5.7	5.2	4.7	4.4	4.1	3.8

* The number of anchoring installations is based upon calculations of hole volumes using ANSI tolerance carbide tipped drill bits, the nominal areas of the reinforcing bars and the stress areas of the threaded rods. These estimates do not account for waste.

ESTIMATING TABLES
A7+
10 Fluid Ounce Cartridge
Number of Anchoring Installations per Cartridge* Using Reinforcing Bar and Threaded Rod with A7+ Adhesive in Solid Concrete

REBAR	DRILL HOLE DIA. INCHES	EMBEDMENT DEPTH IN INCHES (mm)			
		2 (50.8)	4 (101.6)	6 (152.4)	8 (203.2)
#3	7/16	100.1	50.0	33.4	25.0
#4	5/8	49.0	24.5	16.3	12.3
#5	3/4	34.0	17.0	11.3	8.5
#6	7/8	25.0	12.5	8.3	6.3
#7	1	19.2	9.6	6.4	4.8
#8	1-1/8	15.1	7.6	5.0	3.8

* The number of anchoring installations is based upon calculations of hole volumes using ANSI tolerance carbide tipped drill bits, the nominal areas of the reinforcing bars and the stress areas of the threaded rods. These estimates do not account for waste.

Rod In. (mm)	DRILL HOLE DIA. INCHES	EMBEDMENT DEPTH IN INCHES (mm)			
		2 (50.8)	4 (101.6)	6 (152.4)	8 (203.2)
3/8 (9.5)	7/16	100.1	50.0	33.4	25.0
1/2 (12.7)	9/16	60.5	30.3	20.2	15.1
5/8 (15.9)	11/16	40.5	20.3	13.5	10.1
	3/4	34.0	17.0	11.3	8.5
3/4 (19.1)	13/16	29.0	14.5	9.7	7.3
	7/8	25.0	12.5	8.3	6.3
7/8 (22.2)	15/16	21.8	10.9	7.3	5.4
	1	19.2	9.6	6.4	4.8
1 (25.4)	1-1/16	17.0	8.5	5.7	4.2
	1-1/8	15.1	7.6	5.0	3.8